

Features-Specifications Comparison

SPECS / FEATURES	ROTARY® SPOA10	BENDPAK® XPR-10ACX	BENDPAK® ADVANTAGE
Column Construction	Multi-Piece	Single-Piece	√
Carriage Construction	Multi-Piece Formed Steel	Welded Steel Tubing	√
Arm Construction	Multi-Piece Formed Steel	Welded Steel Tubing	√
Top Beam Construction	Multi-Piece Boxed Steel	Single-Piece Boxed Steel	√
Sheave Material	Plastic	Machine Steel	√
Sheave Diameter	3-1/2"	5"	√
Equalizer Cable Diameter	5/16"	3/8"	√
Equalizer Cable Thread Adjustment Range	Up to 2"	Up to 3"	√
Cylinder Stroke	68"	69"	√
Max Rise – Top of Pad in Low Position	72-3/4"	73"	√
Max Rise – Top of Pad in High Position	78-1/4"	76" - 79" - 82"	√
Contact Pad Type	Steel Contact	Reduce Slip Rubber Contact	√
Adapter Type (Standard)	Steel Flip Up	Multi-Stackable	√
Arm Restraints-Gears In Carriage	Yes - Bolted on Gears	Yes - Bolted on Gears	
Lifting Capacity	10,000 lb.	10,000 lb.	
Overall Height	142-2/4"	145"	√
Floor to Overhead Stop Bar	134-3/4"	140"	√
Dimensions – Inside Column	106 ¼"	112"	√
Dimensions – Minimum Pad Height	4 3/4"	4"	√
Drive Thru Clearance	95"	102"	√
Lift Column Configuration	30-Deg. Rotated Columns	30-Deg. Rotated Columns	
Locking Latch Release Design	Single Point	Single Point	
Overhead Padded Switch Bar	Yes	Yes	
Front Arm Reach / Min	21 5/8"	25"	√
Front Arm Reach / Max	43 ½"	46"	√
Rear Arm Reach / Min	34 ½"	42"	√
Rear Arm Reach / Max	58"	60"	√
ETL Certified	Yes	Yes	
Rise Speed	45 Seconds	45 Seconds	
WARRANTY COMPARE	ROTARY®	BENDPAK®	BENDPAK® ADVANTAGE
Structure / Parts	12-Months*	60-Months	√
Hydraulics	12-Months*	12-Months	
Labor	12-Months	12-Months	
*Lifts installed by a Rotary® Authorized Installer get a 2nd year of parts warranty.			

BendPak, BendPak Incorporated and Ranger Products and their respective logos are registered trademarks. Copyright 2005 BendPak Incorporated

BendPak / Ranger, 1645 Lemonwood Dr., Santa Paula, CA 93060
Tel: 1-805-933-9970 Fax: 1-805-933-9160