

Models	VSLW-10	VSLW-8	VSL-10	VSL-8	VSLC-10	VSLC-8	VSL-10	VSL-8
Capacity * (Weight evenly distributed)	1,500 LBS.	1,500 LBS.	1,500 LBS.	1,500 LBS.	1,500 LBS.	1,500 LBS.	1,500 LBS.	1,500 LBS.
Column Height	114" (9'6")	94.5" (7'10.5")	114" (9'6")	94.5" (7'10.5")	114" (9'6")	94.5" (7'10.5")	114" (9'6")	94.5" (7'10.5")
Total Width	148" (12'4")	148" (12'4")	102" (8'6")	102" (8'6")	119" (9'11")	119" (9'11")	102" (8'6")	102" (8'6")
Platform Width	144" (12')	144" (12')	96" (8')	96" (8')	113" (9'5") *	113" (9'5") *	96" (8')	96" (8')
Total Depth *	120" (10')	120" (10')	76" (6'4")	76" (6'4")	120" (10')	120" (10')	120" (10')	120" (10')
Platform Depth	116" (9'8")	116" (9'8")	72" (6')	72" (6')	116" (9'8") *	116" (9'8") *	116" (9'8")	116" (9'8")
Clearance Under Platform at Max Height	84" (7')	67" (5'7")	84" (7')	67" (5'7")	84" (7')	67" (5'7")	84" (7')	67" (5'7")
Lifting Time (feet per minute) 110 volt *	6.5' +/-	6.5' +/-	6.5' +/-	6.5' +/-	6.5' +/-	6.5' +/-	6.5' +/-	6.5' +/-
Lifting Time (feet per minute) 220 volt *	13' +/-	13' +/-	13' +/-	13' +/-	13' +/-	13' +/-	13' +/-	13' +/-
Shipping Weight	1,470 LBS.	1,420 LBS.	925 LBS.	890 LBS.	1,110 LBS.	1,075 LBS.	1,200 LBS.	1,170 LBS.
Shipping Dimensions (LxWxH)	151"x30"x31"	151"x30"x31"	115"x29"x25"	105"x29"x25"	121"x30"x28"	121"x30"x28"	121"x30"x28"	121"x30"x28"

* When weight is EVENLY distributed across platform.

* Lifting times calculated with no weight on platform.

* Platform width and depth measurements are at widest/deepest points on platform on VSLC models.

* Total depth is front of platform to back of the support plate on column base. Does NOT include approach ramps. Add 18" for approach ramps when extended on all models except for VSL (add 13.5").